

Roll Grooving Machine 2" to 12"

Article
150.100.10

	Description
150.100.ST	Steel pipe support
150.60.76K	Knurl wheel(φ60- φ76)
150.89.168K	Knurl wheel(φ89- φ168)
150.219.325K	Knurl wheel(φ219-φ325)
150.60.168P	Pinch roll(φ60- φ168)
150.219.325P	Pinch roll(φ219- φ325)
150.10.GW	Guide wheel



- > This machine is applicable for grooving of the end of 2"-12" steel pipes and 2"-4" plastic-lining pipes.
- > Powered by high-performance gear reducing motor contributing to compact size and low noise.
- > The unique integral hydraulic pump structure and groove depth limitation device ensure high channeling quality plus high working efficiency.
- > Come with a human-friendly handle to facilitate the moving of machine.


▶ Technical Features

- **Processing capability**
 2"-12" (φ57- φ325) steel pipes
 2"-4" (φ57- φ114) plastic-lining pipes
 Max. Wall thickness : 10mm
 Output RPM : 23 rotations/m
- **Driving power**
 Single phase motor, vpltage : 110-240V
 Power Capacity : 1100 - 1500W
 Frequency : 50-60Hz
- **Standard Configuration**
 Steel pipe support, one piece
 A set of 2"-12" Knurl wheel, 3 pieces
 A set of 2"-12" Pinch roll wheel, 2 pieces
 A set of Guide wheel


 00491 5781 123799

Address : Travaza Tools

Amtsgericht Koblenz 56068 koblenz, Solver GMBH, Furst-Abtissinnen-Strabe 6, 53498 Bad Breisig

 www.travazatools.com