

TRA526/TRAG526 ELECTRONIC LEVELING TWO-WAY ROTARY LASER (H-V)

Electronic leveling two-way rotary laser is used for the fitting of ceiling and large curtain wall, square ground leveling, etc. It provides good horizontal, vertical and slope orientation reference for indoor & outdoor decoration and construction

▶ Product Features

- Horizontal or vertical 360° rotary laser
- Electronic leveling, warning when beyond auto-leveling range
- Unbalance warning function
- VWS function
- Adjustable in direction and angle of area scanning
- Dual axis grade scanning function
- Forcible rotation function

▶ Specifications

- Laser wavelength: 635nm (TRA526) ,532 nm (TRAG526)
- Laser class: Class II/III
- Working range(diameter): 600m (TRA526),400m (TRAG526)
- Accuracy: ±0.075mm/m
- Auto-leveling range: ±5°
- Power: Li battery or Ni-MH battery or 3* C battery
- Sealing: IP54
- Size: 6 7/8" x 5 1/2" x 7 5/16" (175x140x186mm)
- Weight: 4.4lbs (2Kg)

▶ Basic kit

- TRA526 main unit, TRA310-3 adapter, TRA312-1 remote control, TRA715 detector, TRA304-3 wall mount, Ni-MH battery, TRA306 glass, TRA307 target, 3# hard carrying case
- TRAG526 main unit, TRA310-3 adapter, TRA312-1 remote control, TRAG715 detector, TRA304-3 wall mount, Ni-MH battery, TRAG306 glass, TRAG307 target, 3# hard carrying case

▶ Applications

ARTICLE #	Model
900.526.05	TRA -526

